



# QUICK SLIDE 32

## Way and Slide Lubricant

### Performance Benefits

- Low frictional characteristics helps eliminate chatter and stick-slip of slides
- High Lubricity helps reduce wear and increases smoothness of sliding action
- Excellent water and aqueous separability extends lubricant life and performance of water dilutable coolants.
- Good adhesiveness prevents removal of lubricant from critical surfaces
- Good rust and corrosion protection helps reduce the deterioration of sliding services and associated maintenance
- Multi-metal compatibility provides protection for ferrous and non-ferrous materials

**QUICK SLIDE 32** is a light viscosity premium-quality slide way lubricant specifically designed for machine tools fitted with combined hydraulic and slideway lubrication systems. It is formulated with high-quality base stocks and a highly engineered additive package designed to reduce stick-slip and chatter under thin film, boundary lubrication conditions allowing smooth uniform motion at travel speeds of today's advanced machinery. **QUICK SLIDE 32** ensures protection of slides and ways while still providing good filterability thereby minimizing reduced flow or plugged applicator filters.

### Applications

**QUICK SLIDE 32** is recommended for machine tools with horizontal slide-ways fitted with combined hydraulic and slideway lubrication systems where a lighter viscosity is required.

### Typical Characteristics

|                                |                                   |
|--------------------------------|-----------------------------------|
| Appearance.....                | Clear, light amber viscous liquid |
| Kinematic Viscosity.....       | 32cSt @ 40°C                      |
| ISO grade.....                 | 32                                |
| Copper Strip (ASTM D 130)..... | 1B                                |
| Flash, PMCC .....              | >200°C                            |

### Recommended Dilutions

**QUICK SLIDE 32** is designed to be applied neat.

### Packaging

**QUICK SLIDE 32** is packaged 5-gallon pails and 55-gallon non-returnable steel drums. Bulk and 310-gallon bins are also available.



*The Next Generation in Metalworking Chemistry*